

Cisco 642-066 Exam

642-066: Advanced Routing and Switching for Field Engineers

Practice Exam: 642-066 Exams

Exam Number/Code: 642-066

Exam Name: Advanced Routing and Switching for Field Engineers

Questions and Answers: 68 Q&As

(Access Routing and LAN Switching)



Exam : [642-066](#)

We provide professional Cisco 642-066 exam information and free demo for 642-066 certification exam's PDF. It is the best and the latest Cisco Practice Exams. Download our 642-066 PDF. We are committed to your ongoing success. Free PassBible 642-066 exam and 642-066 Q&As are constantly being updated and compared to industry standards.

PassBible Test tool's advantages:

High Quality and Value of 642-066 exam

PassBible Cisco Access Routing and LAN Switching 642-066 Practice Questions is developed and finished by Cisco technical team , cover every field of the exam . Besides, we have verified 642-066 answers,almost 100% correct.

100% Guarantee to Pass 642-066 Exam

We promise to give you FULL REFUND if you fail the Access Routing and LAN Switching 642-066 certification(Cisco Certified Network Associate) with the use of our PassBible testing engine.

642-066 Self Test Mode

PassBible provides a simulated and interactive environment where you can test your knowledge and skills about 642-066 to ensure enough assurance in real testing center.

Periodic Updates of PassBible 642-066

Once there is some change on Cisco 642-066 exam, we will update it timely, and the product you buy will be updated within 90 days for free.

Professional and Efficient Service

We offer 7*24 customer support via diverse channels: LIVE CHAT,MAIL.Expecting the communication with you about IT certification.

This 642-066 pdf demo do not include the questions and answers's picture.

Exam : Cisco 642-066

Title : Advanced Routing and Switching for Field Engineers

1. While your MPLS core is using Cisco routers, the core of a company you have acquired is not. After extending your MPLS VPN networks by integrating the cores, you discover that the end-to-end LPS path between PE routers cannot be established.

Which of the following may have caused this problem?

- A. the MTUs do not match
- B. the BGP protocol versions do not match
- C. MPLS is not supported between different vendors
- D. MP-BGP is not supported between different vendors

E. you are using Cisco proprietary TDP in your existing core

Answer: E

2. Refer to the exhibit. For the given configuration, on packets leaving the router on interface FastEthernet0/0 that matches the high traffic class, what will the MPLS experimental bit be set to?

- A. 0
- B. 1
- C. 2
- D. 3
- E. 4
- F. 5

Answer: D

3. Refer to the exhibit. Which show command would display the information in the exhibit?

- A. show policy-map
- B. show policy-map high-priority
- C. show interfaces fastEthernet 0/1 policy-map
- D. show policy-map interfaces fastEthernet 0/1

Answer: D

4. Refer to the exhibit. Which two of these events will be the result of issuing the above command? (Choose two.)

- A. A 64-bit IPv4 prefix will be created.
- B. The route distinguisher will be used to indicate VPN membership.
- C. Extended BGP communities will be used to encode route distinguishers.
- D. A 96-bit VPNv4 prefix will be created and propagated across the IP network.
- E. The route distinguisher is 64 bits and will be prepended to an existing IPv4 route to make it globally unique.

Answer: DE

5. You would like to log messages up to the severity level "Notification." Which three of these commands will you need to issue in order to enable syslog messages to be sent to the syslog server at the IP address 10.1.5.5? (Choose three.)

- A. logging on
- B. logging host 10.1.5.5
- C. logging trap notifications
- D. logging syslog notifications
- E. logging monitor notifications
- F. logging console notifications

Answer: ABC

6. Which two of the following statements are true about HSRP load sharing? (Choose two)

- A. It is achieved by using more than one HSRP group.
- B. It is done in regards to either round robin or weight basis.
- C. It is used to offload the active router in a certain HSRP group.
- D. Single group HSRP is used to achieve more efficient link utilization.
- E. The return traffic is influenced by HSRP load sharing configuration.

Answer: AC

7. Which tool allows a LAN client to determine which router should be the first hop to a particular remote destination, allowing simplified client configuration and processing without creating a single point of failure?

- A. Proxy ARP
- B. Dynamic Routing Protocol
- C. IRDP
- D. VRRP

Answer: D

8. What is the function of the no switchport Catalyst switch interface configuration command?

- A. switches the port from access mode to trunk mode
- B. converts the port from physical Layer 2 port to physical Layer 3 port
- C. enables the interface for Layer 2 switching
- D. disables the interface to prevent traffic flow
- E. clears all the configurations on the interface

Answer: B

9. Refer to the exhibit. Which Catalyst switch configuration would protect a customer network from possible disruption in the case in which an unauthorized switch is added to the network?

A. Switch0#show running-configuration

```
!  
hostname Switch0  
!  
no spanning-tree optimize bpdu transmission  
spanning-tree extend system-id  
!  
interface FastEthernet0/1  
switchport protected
```

B. Switch0#show running-configuration

```
!  
hostname Switch0  
!  
spanning-tree portfast bpduguard default  
no spanning-tree optimize bpdu transmission  
spanning-tree extend system-id  
!  
interface FastEthernet0/1  
spanning-tree guard root
```

C. Switch0#show running-configuration

```
!  
hostname Switch0  
!  
no spanning-tree optimize bpdu transmission  
spanning-tree extend system-id  
!  
interface FastEthernet0/1  
switchport mode access
```

D. Switch0#show running-configuration

```
!  
hostname Switch0  
!  
no spanning-tree optimize bpdu transmission  
spanning-tree extend system-id  
!  
interface FastEthernet0/1  
switchport port-security violation restrict
```

!

Answer: B

10. Cisco Catalyst switches support which three PVLAN port types? (Choose three.)

- A. private
- B. isolated
- C. permanent
- D. community
- E. non-isolated
- F. promiscuous

Answer: BDF

11. You are operating a multi-vendor network and are considering adding redundancy at the access level. Which routing redundancy solution should you implement?

- A. Hot Standby Router Protocol
- B. Gateway Load Balancing Protocol
- C. Virtual Router Redundancy Protocol
- D. both Gateway Load Balancing Protocol and Hot Standby Router Protocol

Answer: C

12. You are troubleshooting an issue which is causing full-sized packets entering the MPLS cloud to be dropped. You have discovered that one of the switches in the MPLS core is not a Cisco switch, but otherwise the MPLS MTU size is set to 1508 bytes on the routers. Based on this information, which of these may be the reason the packets are being dropped?

- A. no switches support oversized packets
- B. by definition, the maximum MTU is 1500 bytes
- C. the switch on your MPLS core that was not produced by Cisco does not support oversized packets
- D. in this situation, the MTU setting is irrelevant; in MPLS the maximum acceptable IP packet size is 1492 bytes
- E. as MPLS VPN labeling increases the size of the packet by 8 bytes, the IP MTU should have been changed to 1508

Answer: C

13. Which two of the following actions must an OSPF NSF-capable router execute after a supervisor engine switchover? (Choose two.)

- A. send the graceful restart message
- B. exchange the complete routing table
- C. re-acquire the link state database content for the network
- D. re-learn the available OSPF neighbors with neighbor relationship restart
- E. re-learn the available OSPF neighbors without neighbor relationship restart

Answer: CE

14. What is the purpose of using VPN hardware acceleration equipment?

- A. to use WebVPN instead of IPsec
- B. to decrease performance and efficiency
- C. to offload encryption functions from a router CPU
- D. to offload encryption functions from router memory

Answer: C

15. While troubleshooting a network outage, you discover that an employee brought a switch from home into the office to connect additional equipment to the network. In order to increase his speed, he connected this switch to both network ports in his office, resulting in a bridge loop. Which of these can you implement to prevent future occurrences of this issue?

- A. RSTP
- B. root guard

C. BPDU guard

D. GLBP

Answer: C

16. When implementing MPLS VPNs between CE and PE routers, which of these statements is correct?

A. If using IS-IS as the PE-CE routing protocol, no redistribution is required.

B. If using static routes between the CE and PE routers, no redistribution of other VPN routes is required.

C. If the PE-CE protocol is not BGP, redistribution of other VPN routes from MP-BGP is required.

D. If RIP is the routing protocol that is used between the PE-CE routers, no redistribution is required, but any other protocol will require redistribution.

E. If using OSPF or EIGRP as the PE-CE routing protocol, redistribution is not required, but any other protocol or static route will require redistribution.

Answer: C

17. What can be specified in IP VACLs?

A. IP source only

B. IP destination only

C. protocol and IP source only

D. IP source, IP destination, and ports

Answer: D

18. Refer to the exhibit. You want to minimize the downtime that results from supervisor engine switchovers on Cisco 6500 Series Switches and Cisco 7600 Series Routers. To achieve this, you are considering deploying a Cisco Nonstop Forwarding with Stateful Switchover solution using OSPF.

In the exhibit you can see the output of the show ip ospf neighbor detail command. Which trait of systems using Cisco Nonstop Forwarding with Stateful Switchover and OSPF is shown in the exhibit output and will impact your plan?

A. Stateful Switchover for Cisco Nonstop Forwarding only works with BGP.

B. Stateful Switchover for Cisco Nonstop Forwarding must be configured on all adjacent routers.

C. Cisco Nonstop Forwarding with Stateful Switchover helper mode is not supported on the adjacent router.

D. Cisco Nonstop Forwarding with Stateful Switchover helper mode for OSPF has been standardized and is supported on the adjacent router.

Answer: D

19. Refer to the exhibit. What is the HSRP state and priority of this interface after HSRP reaches its steady state?

A. Active, Priority 151

B. Active, Priority 201

C. Active, Priority 251

D. Standby, Priority 151

E. Standby, Priority 201

F. Standby, Priority 251

Answer: D

More [642-066 exam](#) information

Related Cisco 642-066 Exams

[642-062](#) *Routing and Switching Solutions for System Engineers*

[642-067](#) *Advanced Routing and Switching for Field Engineers*

[642-061](#) *Routing and Switching Solutions for System Engineers*

[642-055](#) *ARSFE Advanced Routing and Switching for Field Engineers*

[642-054](#) *RSSSE Routing and Switching Solutions for Systems Engineers*

646-003 *Advanced Routing and Switching for Account Managers*

642-066 *Advanced Routing and Switching for Field Engineers*

646-057 *Access Routing and LAN Switching Routing and Switching AM Exam*

642-053 *Access Routing and LAN Switching Routing and Switching SE/FE Exam*

Other Cisco Exams

642-873 642-436 650-621 646-363 642-425 646-588 642-414 642-105

640-553 646-203 350-040 646-057 642-181 351-018 642-681 642-973

646-589 642-901 642-371 642-821