

Cisco 642-971 Exam

642-971: Data Center Networking Infrastructure Design Specialist

Practice Exam: 642-971 Exams

Exam Number/Code: 642-971

Exam Name: Data Center Networking Infrastructure Design Specialist

Questions and Answers: 120 Q&As

(Others)



Exam : [642-971](#)

We provide professional Cisco 642-971 exam information and free demo for 642-971 certification exam's PDF. It is the best and the latest Cisco Practice Exams. Download our 642-971 PDF. We are committed to your ongoing success. Free PassBible 642-971 exam and 642-971 Q&As are constantly being updated and compared to industry standards.

PassBible Test tool's advantages:

High Quality and Value of 642-971 exam

PassBible Cisco Others 642-971 Practice Questions is developed and finished by Cisco technical team , cover every field of the exam . Besides, we have verified 642-971 answers,almost 100% correct.

100% Guarantee to Pass 642-971 Exam

We promise to give you FULL REFUND if you fail the Others 642-971 certification(Cisco Certified Network Associate) with the use of our PassBible testing engine.

642-971 Self Test Mode

PassBible provides a simulated and interactive environment where you can test your knowledge and skills about 642-971 to ensure enough assurance in real testing center.

Periodic Updates of PassBible 642-971

Once there is some change on Cisco 642-971 exam, we will update it timely, and the product you buy will be updated within 90 days for free.

Professional and Efficient Service

We offer 7*24 customer support via diverse channels: LIVE CHAT,MAIL.Expecting the communication with you about IT certification.

This 642-971 pdf demo do not include the questions and answers's picture.

Exam : Cisco 642-971

Title : Data Center Networking Infrastructure Design Specialist

1. Which three of the following service modules can be deployed in redundant pairs with active/active failover? (Choose three.)

- A. ACE
- B. CSM
- C. NAM
- D. IDSM
- E. FWSM
- F. SSLSM

Answer: ADE

2. Which problem can result from end-of-rack designs?

- A. lower reliability
- B. airflow restriction
- C. more devices to manage
- D. complex spanning-tree design

Answer: B

3. You work as the network administrator at TestInside.com. And you are familiar with Cisco product, so as much as you know, which Cisco product is implemented for content routing purposes?

- A. Cisco ACE GSS
- B. Cisco ACE Module
- C. Cisco ACE appliance
- D. Cisco Catalyst 6500 Series Switches

Answer: A

4. How is FCIP traffic marked with DSCP values?

- A. The Cisco MDS 9000 Series Multilayer Switch marks one DSCP value per FCIP tunnel.
- B. The Cisco MDS 9000 Series Multilayer Switch marks two DSCP values per FCIP tunnel.
- C. The aggregation layer Ethernet switch marks one DSCP value per FCIP tunnel.
- D. The aggregation layer Ethernet switch marks two DSCP values per FCIP tunnel.

Answer: B

5. Refer to the exhibit.

Your customer is filling server racks sequentially, filling one rack before beginning the next. Which two access layer designs present challenges in this environment? (Choose two.)

- A. Layer 3
- B. Layer 2 loop-free U
- C. Layer 2 looped square
- D. Layer 2 looped triangle
- E. Layer 2 loop-free inverted U

Answer: AB

6. A very large blade-server deployment has high throughput requirements for both data and storage networks. Which access layer option would you recommend?

- A. blade server Ethernet switch with Cisco SFS 3000 Series Multifabric Switch
- B. blade server InfiniBand switch with Cisco SFS 3000 Series Multifabric Switch
- C. blade server Ethernet switch that is connected to Cisco Catalyst 4948 top-of-rack switch
- D. blade server Ethernet switch that is connected to Cisco Catalyst 6500 Series end-of-rack switch

Answer: B

7. You work as a systems administrator at TestInside.com. You deploy the network for the company by using the default VDC high availability options in the Cisco Nexus 7010 Switch, what will happen then?

- A. The VDC is deleted, and no further action is performed.
- B. If dual supervisors are in use, a supervisor switchover is forced.
- C. The VDC is deleted and then re-created with the startup configuration.
- D. If a single supervisor is in use, a graceful restart is forced.

Answer: B

8. You are a help desk trainee for TestInside.com. One of your customers use the Cisco SFS family of products to provide server-side InfiniBand integration, but as far as you know, which two Cisco products should be implemented to make up the solution? (Choose two.)

- A. Fibre Channel Host Channel Adapters
- B. InfiniBand switch modules
- C. Fibre Channel switch modules
- D. InfiniBand HCA card for IBM and Dell servers

Answer: BD

9. You are a Cisco engineer of TestInside.com. You are configuring the network for the company. The numbers in the ovals stand for the number of ports in each PortChannel(Refer to the exhibit). If VSS is deployed in the top four switches, as far as you know, how many ports at most that the virtual PortChannel in the core can have ?

- A. two
- B. four
- C. six
- D. eight

Answer: D

10. Your customer plans to deploy FWSM and IDSM modules in the aggregation layer. Which design should you avoid?

- A. Layer 3
- B. InfiniBand
- C. Layer 2 loop-free
- D. Layer 2 looped square
- E. Layer 2 looped triangle

Answer: A

11. Which data center network-architecture change is a result of the adoption of blade and 1-RU server technologies?

- A. Layer 3 fault domains growing larger
- B. Layer 2 fault domains growing larger
- C. Layer 3 fault domains growing smaller
- D. Layer 2 fault domains growing smaller

Answer: B

12. What advantage does InfiniBand have over Gigabit Ethernet in HPC environments?

- A. lower latency
- B. simpler cabling
- C. longer distance support
- D. more sophisticated traffic management

Answer: A

13. You work as a systems administrator at TestInside.com. In order to realize to service multicast traffic in a data center environment, what three of following options are effective ways? (Choose three.)

- A. deploying VRFs per address family
- B. configuring service modules in transparent or bridged mode
- C. configuring IGMP/PIM in the Cisco Catalyst 6500 Series FWSM
- D. configuring IGMP/PIM in the MSFC on a Cisco Catalyst 6500 switch

Answer: BCD

14. You are a Cisco engineer of TestInside.com. You are implementing the Cisco Nexus environment for the company, so which two are requirements of FCoE in it? (Choose two.)

- A. Spanning Tree Protocol
- B. Use of jumbo frames
- C. TCP-driven retransmissions for flow control
- D. IEEE 802.3x extensions to enable lossless Ethernet

Answer: BD

15. Which two security vulnerabilities does the FWSM application inspection engine mitigate? (Choose two.)

- A. DoS attacks
- B. DDoS attacks
- C. SQL injection
- D. cookie altering
- E. web server worms

Answer: CD

16. You are the senior desktop administrator for TestInside.com. A customer met a trouble: A failure occurs on one of the access layer uplinks(Refer to the exhibit). With your experience, which Layer 2 topology can cause a break in connectivity between the FWSMs?

- A. looped square
- B. looped triangle
- C. loop-free U
- D. loop-free inverted U

Answer: C

17. Refer to the exhibit. Each letter (A-D) represents a model for placement of a default gateway. Which model allows the maximum number of application and security services?

- A. model A
- B. model B
- C. model C
- D. model D

Answer: C

18. Refer to the exhibit. What do you need to configure to prevent spanning-tree loops from occurring between the two FWSMs?

- A. FWSMs in transparent mode
- B. ethertype ACLs to allow BPDUs
- C. FWSMs in multiple-context mode
- D. failover and state interfaces on the same VLAN

Answer: B

19. You are the senior desktop administrator for TestInside.com. You are deploying network for the company. With your experience, which of following two Cisco service modules can be implemented in redundant pairs with active-active failover? (Choose two.)

- A. Cisco network analysis module
- B. Cisco ACE Application Control Engine
- C. Cisco Firewall Services Module (FWSM)
- D. Cisco Catalyst 6500 Series SSL Services Module (CVDM-SSLSM)

Answer: BC

20. Which service module configuration is recommended to automatically detect and block traffic from malicious hosts?

- A. FWSM
- B. IDSM that is deployed in IDS mode
- C. IDSM that is deployed in IPS mode
- D. FWSM that is coupled with the NAM

Answer: C

Related Cisco 642-971 Exams

[642-524](#) *Securing Networks with ASA Foundation*

[642-436](#) *Cisco Voice over IP (CVOICE)*

[642-972](#) *Data Center Application Services Design*

[650-175](#) *SMBAM SMB Specialization for Account Managers*

[646-223](#) *Unified Communications Express AM*

[642-504](#) *Securing Networks with Cisco Routers and Switches*

[642-145](#) *Implementing Cisco IOS Unified Communications Advanced*

[642-456](#) *Implementing Cisco Unified Communications Manager Part 2 (CIPT2 v6.0)*

[642-741](#) *Implementing Cisco Unified Wireless Voice Networks*

[642-426](#) *Troubleshooting Unified Communications (TUC)*

[640-460](#) *IIUC Implementing Cisco IOS Unified Communications (IIUC)*

[642-383](#) *Cisco Express Foundation for Field Engineers*

[642-731](#) *Conducting Cisco Unified Wireless Site Survey*

[650-180](#) *SMBEN SMB Solutions for Engineers*

[646-230](#) *Advanced Unified Communications AM*

[646-563](#) *Advanced Security for Account Managers Exam*

[642-373](#) *Cisco Express Foundation for Systems Engineers*

[646-363](#) *Cisco Express Foundation for Account Managers*

[642-975](#) *Cisco Data Center Application Services Implementation*

[646-656](#) *Wide Area Application Services for Account Managers*

Other Cisco Exams

[642-143](#) [642-892](#) [642-975](#) [650-173](#) [642-145](#) [642-691](#) [646-202](#) [350-022](#)

[642-415](#) [642-973](#) [642-551](#) [646-204](#) [642-453](#) [642-964](#) [642-243](#) [642-545](#)

[646-588](#) [646-653](#) [642-741](#) [642-515](#)