

## Nortel 920-451 Exam

**920-451: ncde callpilot 2.x/3.0 unified messaging**

**Practice Exam:** 920-451 Exams

**Exam Number/Code:** 920-451

**Exam Name:** ncde callpilot 2.x/3.0 unified messaging

**Questions and Answers:** 56 Q&As

**( Other Nortel Certification )**



Exam : [920-451](#)

We provide professional Nortel 920-451 exam information and free demo for 920-451 certification exam's PDF. It is the best and the latest Nortel Practice Exams. Download our 920-451 PDF. We are committed to your ongoing success. Free PassBible 920-451 exam and 920-451 Q&As are constantly being updated and compared to industry standards.

### **PassBible Test tool's advantages:**

#### **High Quality and Value of 920-451 exam**

PassBible Nortel Other Nortel Certification 920-451 Practice Questions is developed and finished by Nortel technical team , cover every field of the exam . Besides, we have verified 920-451 answers,almost 100% correct.

#### **100% Guarantee to Pass 920-451 Exam**

We promise to give you FULL REFUND if you fail the Other Nortel Certification 920-451 certification(Nortel Certified Network Associate) with the use of our PassBible testing engine.

#### **920-451 Self Test Mode**

PassBible provides a simulated and interactive environment where you can test your knowledge and skills about 920-451 to ensure enough assurance in real testing center.

#### **Periodic Updates of PassBible 920-451**

Once there is some change on Nortel 920-451 exam, we will update it timely, and the product you buy will be updated within 90 days for free.

#### **Professional and Efficient Service**

We offer 7\*24 customer support via diverse channels: LIVE CHAT,MAIL.Expecting the communication with you about IT certification.

This 920-451 pdf demo do not include the questions and answers's picture.

Exam : Nortel 920-451

Title : NCDE Callpilot 2.x/3.0 Unified Messaging

Version : Demo

1. A customer has a network that contains several Communication Server (CS) 1000 RIs 4.0 systems. They are networked together via Virtual Trunks. The customer has limited bandwidth on the WAN links between sites and has an Optimized WAN link to carry Voice calls that use G.729A. Which configuration setup will ensure that G.729 is always used on a virtual trunk call between sites?

A. No extra configuration is needed. Virtual Trunk calls always use G.729A CODEC.

B. ? configure the virtual route to be in same zone as voice gateway channels and IP sets ? verify that the customer has G.729A as part of CODEC profile ? verify all zones at the site are configured with best quality for intrazone calls

and best bandwidth for interzone calls

C. ? virtual route is configured to be in different zone than the voice gateway channels and IP sets ? verify the customer has G.729A as part of CODEC profile ? ensure all zones at the site are configured with best quality for intrazone calls and best quality for interzone calls

D. ? the virtual route is configured to be in a different zone than voice gateway channels and IP Sets for each system ? verify the customer has G.729A as part of CODEC profile ? ensure all zones at the site are configured with best quality for intrazone calls and best bandwidth for interzone calls

Answer: D

2. A customer has a Communication Server (CS) 1000 RIs. 4.0 that they want to network with two other sites using the corporate WAN. Why must zones be configured with Element Manager before the Virtual Routes? (Choose two.)

A. Zones determine NCOS privileges on a given trunk.

B. Zones govern trunk groupings for TGAR assignment.

C. Zones help determine Best Bandwidth CODEC per virtual trunk call.

D. Zones manipulate CODEC selections and assigns bandwidth to a route.

E. Zones provide call blocking based on Bandwidth defined for inter- and intra-zone calls.

Answer: CE

3. A company has two Communication Server (CS) 1000 RIs. 4.0 systems networked together with the following components: ? 800 IP Phone 2002 telephones at site A ? 600 IP Phone 2004 and 300 IP Phone 2002 telephones at site B Network Virtual Office is configured to enable IP telephone users to use their customized settings (i.e., autodial, key layout, etc.) on every IP telephone in the CS network. They want to use the Virtual Office Automatic Logout (VO\_ALO) feature to log out all IP telephone users from their IP telephones automatically. To configure the VO\_ALO feature, which task should you perform using the Command Line Interface (CLI)?

A. Access Overlay LD 15, then enable VOLA.

B. Access Overlay LD 15, then enable VO\_ALO.

C. Access Overlay LD 11, then enable VO\_ALO for each Terminal Number (TN).

D. Access Overlay LD 11, then enable Virtual Office Login Allowed (VOLA) for each TN.

Answer: B

4. A company plans to have a Communication Server (CS) 1000 RIs. 4.0 Main Office (MO) site with one Media Gateway 1000B branch office (BO) site. The BO and MO will be connected via virtual trunks. Users at both sites will use Coordinated Dialing Plans (CDPs) to dial between the sites. They want long distance and CDP calls originating from the BO to route to the MO. All long distance calls will be tagged as international calls originating from the BO. They have no plans to expand the BO in the future. What is the most efficient way of routing calls from the BO?

A. In the Gatekeeper, select the BO as the tandem endpoint for the MO.

B. In the Gatekeeper, select the MO as the tandem endpoint for the MO.

C. In the Gatekeeper, select the MO as the default route for CDP and international calls. All NPA ranges will need to be defined under the MO.

D. In the Gatekeeper, all Numbering Plan Areas (NPAs), international numbers, and CDP steering codes should be defined under the MO.

Answer: C

5. A customer is installing a Communication Server (CS) 1000M-SG RIs. 4.0 at their Main Office (MO). They have a 10-member network using the corporate WAN and a Primary Gatekeeper. They want to use an Alternate Gatekeeper for redundancy. When are the Alternate Gatekeepers programmed? (Choose two.)

A. during software installation and initial setup of the Signaling Server

B. in Overlay LD 17 (Configuration) under the ADAN as an ELAN IP address

C. in Overlay LD 117 (Configuration2) as an Embedded LAN (ELAN) IP address

D. in Element Manager under the Signaling Server setting after the software has been installed

Answer: AD

6. A customer has installed a Communication Server (CS) 1000M RIs 4.0 system. Currently all 800 IP telephones at

the site are registered to a single Signaling Server . This site has three installed media cards. What component(s) should be added at the site to ensure full redundancy for IP telephones?

- A. an additional Signaling Server must be installed and set as Failsafe
- B. an additional Signaling Server must be installed and programmed as Follower
- C. an additional Signaling Server must be installed and programmed as Alternate
- D. two additional media cards to ensure that all 800 IP telephones can register to media cards if the Leader Signaling Server fails

Answer: B

7. A company has a two-site Communication Server (CS) 1000 RIs. 4.0 system (site A and B) providing IP-PBX services. Both systems are networked via a managed IP backbone. One system is a CS 1000 RIs. 3.0 Main Office (MO) and the other is a Media Gateway 1000 RIs. 4.0 branch office (BO). You configure the networked systems to enable the following: ? Users at the MO to call BO workstations by dialing 49xxx. ? Users at the BO to call MO workstations by dialing 2xxx. Which initial configuration task should you perform using Element Manager (EM)?

- A. Configure an LSC of 2 and a DSC of 49 in the MO.
- B. Configure a DSC of 2 in the MO and configure VNR in the BO.
- C. Configure a DSC of 49 in the MO and configure Vacant Number Routing (VNR) in the BO.
- D. Configure a Local Steering Code (LSC) of 49 and a Distant Steering Code (DSC) of 2 in the BO.

Answer: C

8. A customer has just installed a Communication Server (CS) 1000M system. The CS 1000M is networked via the corporate WAN with several offices around the country. BARS is configured correctly for all telephones to use this route and the Virtual Trunks show IDLE. Traffic studies have shown that the majority of calls to remote locations are going out via the PSTN route instead of the virtual route. What in the configuration could cause this situation?

- A. CODEC is not assigned to the Virtual Trunk Route
- B. Bandwidth is incorrectly defined in the Zone Basic Property
- C. CODEC not defined for the zone in the Zone Basic Property
- D. Bandwidth is not defined for the Virtual Trunk Route and member trunks

Answer: B

9. A customer has installed two Communication Server (CS) 1000M RIs. 4.0 systems networked over the corporate WAN. Some of the system management functions of the CS 1000M can be performed by the Command Line Interface (CLI) as well as Element Manager. Which is a false statement regarding the use of Element Manager (EM) over the CLI?

- A. EM provides for drop down menus for prompt choices.
- B. EM provides full text descriptions of parameters and acronyms.
- C. EM allows the programmer to use the LD commands as well as using menus.
- D. EM increases speed and efficiency by organizing parameters to logical groups.

Answer: C

10. A company has a multi-site Communication Server (CS) 1000M-Chassis RIs. 4.0 system. If one of the Media Gateways goes into Survival Mode, they want Manual Control to restore the Media Gateway into Normal Mode. In Overlay LD 117, which command should you use to achieve this configuration?

- A. Chg Surv &lt;port> No
- B. Chg Surv &lt;port> Yes
- C. Chg Autosb &lt;port> No
- D. Chg Autosb &lt;port> yes
- E. Chg Swoto &lt;port> &lt;value>

Answer: C

More [920-451 exam](#) information

<u>922-109</u>	<i>Communications Server 1000 RIs.6.0 BARS/NARS</i>
<u>922-101</u>	<i>Communication Server 1000 Linux Platform Architecture</i>
<u>922-111</u>	<i>Communication Server 1000 to RIs.6.0 Upgrades for Technicia</i>
<u>922-081</u>	<i>CallPilot RIs.5.0 Networking</i>
<u>920-457</u>	<i>CallPilot Ris.4.0 Unified Messaging Exam</i>
<u>922-104</u>	<i>Communication Server 1000 RIs.6.0 Upgrades for Engineers</i>
<u>922-071</u>	<i>BCM50 RIs.3.0 &amp; BCM200/400 RIs.4.0 Config &amp; Maintenance</i>
<u>920-110</u>	<i>NNCSS SL-100 Maintenance Certification Exam</i>
<u>922-098</u>	<i>Communication Server 1000 RIs.5.0 Troubleshooting</i>
<u>920-806</u>	<i>Nortel Advanced Data Networking Technology</i>
<u>920-805</u>	<i>Nortel Data Networking Technology</i>
<u>920-220</u>	<i>Nortel Converged Campus ERS Solution</i>
<u>920-502</u>	<i>nncss-optera metro 3000</i>
<u>920-569</u>	<i>nncds-optera metro solutions</i>
<u>920-246</u>	<i>Nortel WLAN 2300 Ris.5.0 Implementation &amp; Management</i>
<u>920-520</u>	<i>Nortel Agile Communication Environment (ACE) RIs. 1.x Design &amp; Engineering</i>
<u>922-094</u>	<i>Communication Server 1000 RIs.5.0 Dialing Plan Design &amp; IP</i>
<u>922-099</u>	<i>Communication Server 1000 RIs.5.0 Linux Platform Base &amp; App</i>
<u>920-199</u>	<i>BCM50 Ris. 2.0 &amp; BCM200/400 Ris. 4.0 ICM</i>
<u>920-111</u>	<i>NCSS-VoIP Communication Server(CS)2100</i>

#### **Other Nortel Exams**

<u>922-092</u>	<u>920-136</u>	<u>920-521</u>	<u>920-261</u>	<u>920-360</u>	<u>920-106</u>	<u>920-191</u>	<u>920-170</u>
<u>920-804</u>	<u>922-103</u>	<u>920-166</u>	<u>920-532</u>	<u>920-172</u>	<u>920-341</u>	<u>920-335</u>	<u>920-247</u>
<u>920-239</u>	<u>920-447</u>	<u>920-110</u>	<u>920-461</u>				